

## Approved Products List – 6/6/2022

The Dirt & Gravel Road Maintenance Program was founded on solid environmental principles. One of these principles is the program's strict limitations on the use of products that may cause damage to the environment in any way. Listed here are the products approved for purchase and use with program funding. The program does not endorse these or any other individual products.

<b>PETROLEUM EMULSION DUST SUPPRESSANT</b>			
<b>PRODUCT NAME</b>	<b>DISTRIBUTOR</b>	<b>TYPE</b>	<b>APPROVED APPLICATION RATE</b>
Dust Clear G	Midland Asphalt Materials, Inc.  88 Barrett Road Woodland, PA 16881 Phone: (814) 857-7635  <a href="http://www.midlandasphalt.com">www.midlandasphalt.com</a>	Tall Oil Emulsion	2 applications of 0.2 gal/yd <sup>2</sup> 15 minutes apart
Resinator	West Gary Momar Incorporated 1830 Ellsworth Industrial Dr. Atlanta Georgia, 30318 Phone: (404) 355-4580  <a href="mailto:West.gary@momar.com">West.gary@momar.com</a>	Petroleum Emulsion	0.5 gal/yd <sup>2</sup> of 1:4 emulsion to water or more dilute
Ultrabond 2000	Scott Reefer Environmental Energy Solutions, LLC 10027 Rte. 403 Hwy South Seward, PA 15954 Phone: (814) 446-5625  <a href="mailto:sreefer@eesolutionsllc.com">sreefer@eesolutionsllc.com</a>	Petroleum Emulsion	2 applications of 0.25 gal/yd <sup>2</sup> of 1:5 emulsion to water or more dilute

<b>SYNTHETIC FLUID DUST SUPPRESSANT</b>			
<b>PRODUCT NAME</b>	<b>DISTRIBUTOR</b>	<b>TYPE</b>	<b>APPROVED APPLICATION RATE</b>
EnviroKleen	Lynn Cielec Midwest Ind. Supply 1101 3rd Street S.E. Canton, OH 44711  Phone: (800) 321-0699  Cell: (303) 417-2069 Fax: (330) 456-3247  <a href="http://www.midwestind.com">www.midwestind.com</a>	Synthetic Fluid	0.125 gal/yd <sup>2</sup> Two passes are required for a total application rate of 0.250 gal/yd <sup>2</sup> . No dilution.
DustLess	Rose Cyr Global Environmental Solutions, LLC 395 Main St., Unit 7 Salem, NH 03079  Phone: (978) 388-3312 Fax: (603) 362-9207  <a href="http://www.GlobalEnvironmentalSolutions.com">www.GlobalEnvironmentalSolutions.com</a>	Synthetic Fluid	Min = 0.18 gal/yd <sup>2</sup> . Max = 0.45 gal/yd <sup>2</sup> No dilution.

**ACRYLIC POLYMER DUST SUPPRESSANT**

<b>PRODUCT NAME</b>	<b>DISTRIBUTOR</b>	<b>TYPE</b>	<b>APPROVED APPLICATION RATE</b>
DustREADY 49	Gary Blenda Envirotech Services Phone: (216) 401-9522 <a href="mailto:gblenda@envirotechservices.com">gblenda@envirotechservices.com</a>	Acrylic	1:4 dilution of product to water. Two applications of 0.25 gal/yd <sup>2</sup>

**SOIL STABILIZER**

<b>PRODUCT NAME</b>	<b>DISTRIBUTOR</b>	<b>TYPE</b>	<b>APPROVED APPLICATION RATE</b>
EcoRoads	Colby Price EnviRemend Construction 6480 Beach Dr. SW Ocean Isle Beach, NC 28469 Phone: (910) 712-1081 <a href="mailto:cprice@enviremed.net">cprice@enviremed.net</a>	Enzyme	diluted with water at ratio of not < 250 to 1 evenly mixed with subgrade to optimum moisture

**ROAD FILL MATERIALS**

<b>PRODUCT NAME</b>	<b>DISTRIBUTOR</b>	<b>TYPE</b>	
Harsco Minerals	Bob Onyshko Harsco Minerals Phone: (717) 506-2071 1-800-850-0527 <a href="mailto:ronyshko@harsco.com">ronyshko@harsco.com</a>	Recycled Steel Slag	Road Fill Material

The publishers of this publication gratefully acknowledge the financial support of the PA State Conservation Commission. For additional information or assistance, contact: Center for Dirt & Gravel Roads Studies, Penn State University, 215 Transportation Research Building, University Park, PA 16802 (Toll-Free Phone: 1-866-668-6683, Fax: 814-863-6787, Email: [dirtandgravel@psu.edu](mailto:dirtandgravel@psu.edu)). Additional copies available on our website at: [www.dirtandgravelroads.org](http://www.dirtandgravelroads.org). © 2022 Penn State Center for Dirt and Gravel Roads. All rights reserved.